

Package: spinyReg (via r-universe)

November 1, 2024

Type Package

Title Sparse Generative Model and Its EM Algorithm

Version 0.1-0

Date 2015-09-05

Author Charles Bouveyron, Julien Chiquet, Pierre Latouche,
Pierre-Alexandre Mattei

Maintainer Julien Chiquet <julien.chiquet@gmail.com>

Description Implements a generative model that uses a spike-and-slab like prior distribution obtained by multiplying a deterministic binary vector. Such a model allows an EM algorithm, optimizing a type-II log-likelihood.

License GPL (>= 2)

Imports methods

Repository/R-Forge/Project spinyreg

Repository/R-Forge/Revision 11

Repository/R-Forge/DateTimeStamp 2015-09-07 10:50:53

Date/Publication 2015-09-07 18:18:03

NeedsCompilation no

Repository <https://jchiquet.r-universe.dev>

RemoteUrl <https://github.com/cran/spinyReg>

RemoteRef HEAD

RemoteSha 547f0f4d33bf4ca8cbdc945d2d0950bb131753a3

Contents

spinyReg	2
spinyreg-class	3
Index	4

 spinyReg

spinyReg

Description

Computethe path of solution of a spinyReg fit.

Usage

```
spinyreg(X, Y, alpha = 0.1, gamma = 1, z = rep(1, ncol(X)),
  intercept = TRUE, normalize = TRUE, verbose = 1, recovery = TRUE,
  maxit = 1000, eps = 1e-10)
```

Arguments

X	matrix of features. Do NOT include intercept.
Y	matrix of responses.
alpha	numeric scalar; prior value for the alpha parameter (see the model's details). Default is 0.1.
gamma	numeric scalar; prior value for the gamma parameter (see the model's details). Default is 1.
z	numeric vector; prior support of active variable. Default is rep(1, p), meaning all variable activated
intercept	logical; indicates if a vector of intercepts should be included in the model. Default is TRUE.
normalize	logical; indicates if predictor variables should be normalized to have unit L2 norm before fitting. Default is TRUE.
verbose	integer; activate verbose mode from '0' (nothing) to '2' (detailed output). should be included in the model. Default is TRUE.
recovery	logical; indicates if the full path of models should be inspected for model selection. Default is TRUE.
maxit	integer; the maximal number of iteration (i.e. number of alternated optimization between each parameter) in the Expectation/Maximization algorithm.
eps	a threshold for convergence. Default is 1e-10.

Value

an object with class spinyreg, see the documentation page [spinyreg](#) for details.

See Also

See also [spinyreg](#).

Examples

```
## Not run:
data <- read.table(file="http://statweb.stanford.edu/~tibs/ElemStatLearn/datasets/prostate.data")
x <- data[, 1:8]
y <- data[, 9]
out <- spinyreg(x,y,verbose=2)

## End(Not run)
```

spinyreg-class	Class "spinyreg"
----------------	------------------

Description

Class of object returned by the **spinyreg** function.

Slots

coefficients: numeric vector of coefficients with respect to the original input. Contains the intercept if the model owns any.

alpha: numeric scalar.

gamma: numeric scalar.

normx: Vector (class "numeric") containing the square root of the sum of squares of each column of the design matrix.

residuals: Vector of residuals.

r.squared: scalar giving the coefficient of determination.

fitted: Vector of fitted values.

monitoring: List (class "list") which contains various indicators dealing with the optimization process.

intercept: Logical which indicates if a intercept is included in the model.

Methods

This class comes with the usual `predict(object, newx, ...)`, `fitted(object, ...)`, `residuals(object, ...)`, `coefficients(object, ...)`, `print(object, ...)` and `show(object)` generic (undocumented) methods.

Index

- * **class**
 - spinyreg-class, [3](#)
- * **models,**
 - spinyReg, [2](#)
- * **regression**
 - spinyReg, [2](#)

- coefficients, spinyreg-method
(spinyreg-class), [3](#)

- fitted, spinyreg-method
(spinyreg-class), [3](#)

- predict, spinyreg-method
(spinyreg-class), [3](#)
- print, spinyreg-method (spinyreg-class),
[3](#)

- residuals, spinyreg-method
(spinyreg-class), [3](#)

- show, spinyreg-method (spinyreg-class), [3](#)
- spinyReg, [2](#)
- spinyreg, [2](#)
- spinyreg (spinyReg), [2](#)
- spinyreg-class, [3](#)